

RIELLO S.p.A
Sede legale e amministrativa
Via Ing. Pilade Riello, 7
37045 Legnago (VR)

Società con Socio Unico soggetta
alla direzione e coordinamento
di Carrier Global Corporation

Cap. soc. € 7.117.400,00 i.v.
Reg. delle Imp. di Verona N. 02641790239
C.F. e P.IVA 02641790239

www.berettaclima.it



DECLARATION OF CONFORMITY

The company **Riello S.p.A. Via Ing. Pilade Riello 7, 37045 Legnago (Verona), ITALY** declare, under its sole responsibility, that the product:

HYDRAULIC KIT HYBRID

It has been designed to be installed outdoors as well, in partially protected areas, with minimum temperatures above 0°C. However, it remains the installer's responsibility to absolutely prevent the water inside the HYBRID HYDRAULIC KIT and the piping from freezing.

In "Cooling" operating mode, as stated in the Manual, the maximum ambient air temperature (D.B.) is 32°C(*). Above this limit, condensation may form on the external surface of the hydraulic kit.

(*). Maximum limit for dew point < 24°C based on the following conditions:

- pipe length: 5 m
- height difference: 0 m
- maximum airflow rate

Legnago, January 16, 2026

Riello S.p.A.

Director Engineering

Marco de Nardis